

Kunststoff-Recyclingverfahren und Verfahren zur Herstellung von Kunststoffwerkstoffen

Publication number: DE19625110 (A1)

Publication date: 1997-12-18

Inventor(s): SCHALLENBERG GUENTER [DE] +

Applicant(s): FINACOR ANSTALT [LI] +

Classification:

- international: **B29B17/00; C08J11/06; C08L101/00; B29B17/00; C08J11/00; C08L101/00;** (IPC1-7): B29B17/00; C07C53/00; C07C53/126; C07C57/00; C07C69/22; C07C69/52

- European: B29B17/00D

Application number: DE19961025110 19960617


Priority number(s): DE19961025110 19960617

Also published as:

 ZA9704604 (A)
 US6274637 (B1)
 TR9802621 (T2)
 SK285516 (B6)
 PT906365 (E)

more >>

Cited documents:

 DE3715646 (A1)

Abstract of DE 19625110 (A1)

The invention relates to a process for recycling and producing plastics, plastics mixtures or from sorted and unsorted plastic waste, in which a) a substrate material A, which comprises a newly produced plastic material or plastic waste material comprising a uniform single type of plastic or various plastics, a material of any or unknown composition X and an additive Z selected from among fatty acids, fatty acid-containing mixtures of natural or synthetic origin, fatty acid derivatives and fatty alcohols releasing fatty acids in the process conditions are mixed together, where A and X together, in relation to the total volume, contain at least such a quantity of plastic that the non-plastic components are bonded with the formation of a homogenous or partially homogenous mass; b) said mixture is transported by a conveyor and subjected along the conveyor path to a multi-step heat treatment in sections while continuing to be subjected to mechanical mixing, kneading or pressing, where the temperatures in the various steps lie mutually independently in a range from 60 to 400 DEG C; and c) the heat-treated mixture is ejected through a nozzle for further treatment or shaping.

~~~~~  
 Data supplied from the **espacenet** database — Worldwide